


» KTQ77/FLEX Motherboard «



FLEX ATX Motherboard with 3rd Generation Intel® i7-,i5,-i3 2Core and 4Core CPUs & Intel® Q77 Chipset

- » Long term available embedded FLEX-ATX motherboard
- » High CPU and graphics performance for 3 independent displays
- » 2x Display Port for flexible, high resolution display drive
- » Up to 32 GB DDR3 RAM
- » 4x USB 3.0 & 10x USB 2.0, 6x SATA (incl. 2x SATA III), 3x GbE-LAN with AMT 8.0
- » mSATA interface highspeed state of the art SSD storage, 2x PCI 32 bits/33MHz (on Flex)
- » Intel® AMT 8.0 support
- » PCIe 3.0 support

KTQ77 Flex - Motherboard

3rd Generation Intel® i7-,i5,-i3 2Core and 4Core CPUs & Intel® Q77 Chipset

Typical Applications

- » **Digital Signage:** High graphics performance & multi display support
- » **Gaming/POS/POI:** High graphics and high CPU performance
- » **Medical:** High Graphics performance & longevity
- » **Industrial Automation:** wide range of I/Os & longevity
- » **Future-oriented Devices** due to Display Port and mSATA/compact SSD support



Rear I/Os

Technical Information

Features	KTQ77 FLEX Motherboards
CPU	Intel® Core i7/i5/i3 2C
CPU Clock	Up to 3.8 GHz
Front Side Bus	DMI 2.0 support; Four lanes in each direction; Up to 20 Gb/s each direction, full duplex. DMI interface to PCH is supported
Chipset	Intel® Q77
DRAM	Up to 8 GB DDR3, 4x (max. 32GB), 1067/1333/1600 MHz support
Graphics Controller	integrated into CPU
SATA	6x SATA interfaces (4x SATA150/300 and 2x SATA600) w. RAID 0/1/5/10
USB	4x USB 3.0 & 10 USB 2.0
Ethernet	3x GbE-LAN, one LAN controller supporting Intel® AMT 8.0
Form Factor	Flex: 22,86 cm x 19,05 cm (9" x 7,5")
Available I/Os	PCIe 3.0, 2x PCI 32bits/33MHz (on FLEX), 1x Mini-PCIe, 1x mSATA, 4x COM, Internal PS2 Mouse/Keyboard connector
Graphic Interface	1x PCIe x4, 1x PCIe x16, 2x Display port, 1x CRT
Rear I/O	DB9 serial port, DB15 VGA , Audio stacked 2x3 mini Jack tower, 6x USB, 2x Display port, 3x RJ45 LAN
Temperature	Operating 0°C - 60°C (32°F - 140°F)
Special Feature	Multi purpose HDD RAID 0,1,5,10 Support, GPIO, LPT, HD Audio, Mini-PCIe; AMT 8.0, mSATA interface for SSD storage, TPM 1.2 support, KT embedded feature connector with ADC, DAC up to 160 GPIO, up to 3 independent displays supported
Additional	Up to 7 years availability

CORPORATE OFFICES

Europe, Middle East & Africa

Oskar-von-Miller-Str. 1
85386 Eching/Munich
Germany
Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 219
info@kontron.com

North America

14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
info@us.kontron.com

Asia Pacific

17 Building,Block #1,ABP.
188 Southern West 4th Ring Road
Beijing 100070, P.R.China
Tel.: + 86 10 63751188
Fax: + 86 10 83682438
info@kontron.cn

